Philips
RG6 coaxial cable

6 ft

F-Type Male to Male

SWV2234

Ensure a reliable connection

with this F type coaxial cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality
- Nickel-plated connectors for reliable contact

Enjoy good audio quality
- High purity copper conductor for reliable signal transfer

Protects against signal loss
- Bare copper shielding

Easy installation
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability
- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

RG6 coaxial cable
6 ft F-Type Male to Male

SWV2234/17

Specifications

Packaging
- EAN/UPC/GTIN: 6 09585 12284 0
- Quantity: 1
- Gross Weight: 0.100 kg
- Tare Weight: 0.010 kg
- Net Weight: 0.090 kg
- Length: 19.60 cm
- Width: 9.50 cm
- Height: 4.30 cm

Inner Carton
- EAN/UPC/GTIN: 1 06 09585 12284 7
- Quantity: 6
- Gross Weight: 0.590 kg
- Tare Weight: 0.050 kg
- Net Weight: 0.540 kg
- Length (cm): 28.10 cm
- Width (cm): 13.70 cm
- Height (cm): 12.40 cm

Outer Carton
- EAN/UPC/GTIN: 2 06 09585 12284 4
- Quantity: 72
- Gross Weight: 7.130 kg
- Tare Weight: 0.650 kg
- Net Weight: 6.480 kg
- Length (cm): 55.20 cm
- Width (cm): 34.30 cm
- Height (cm): 39.40 cm

Product highlights

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Bare copper shielding
Bare copper shielding protects against signal loss.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug
Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors
Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Issue date 2007-11-30
Version: 1.0
12 NC: 8670 000 26034
UPC: 6 09585 12284 0

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com